



BD5 SERIES BUSINESS DIGITAL RADIO



BD502i

BD552i

SIMPLE, ROBUST, CLEAR-VOICE



Hytera's BD5i series two-way radio is the compact device that provides professional communications and easily operated. Today, communication tools are the key to improved efficiency. When we ask for clear voice, it means a reliable talk, easy-to-hear and understand. Long battery life helps you to maintain control. A rugged and robust device takes the worry out of communicating. High-performance but simple operation will make everything go easy.

Hytera understands customers' requirements and meets them all in one. With lightweight, easy-operation, excellent performance, long battery life and reliability. We redefine a business radio using Hytera digital technology and quickly responding to what you need.

EXCELLENT PERFORMANCE

With innovative design, BD5i series has better performance than analog radios. Excellent reception ability makes talk range further extended. DMR digital radios with good performance and negligible interference, provide stable communication.

RUGGED AND RELIABLE

BD502i/BD552i is designed and tested to meet Military Standards 810 G, including temperature shock, vibration, high & low temperature and humidity. IP54 dust and water-proof design guarantees the reliability in different environments. Based on TDMA technology, the radio can work longer, up to 22 hours in digital mode.

CLEAR VOICE

With digital encoding and correction technology, human voice is transmitted clearer without noise, even over greater distance. This is a new experience of improved audio quality.



ANTENNA
Enhance signal receiving ability.

CHANNEL KNOB
Support 16 channels that are easily changed.

LED INDICATOR
Show the radio receiving and transmitting status as green light and red light.

SPEAKER AND MICROPHONE
Provide clear receive and transmit audio.

LIMITLESS CHANNEL SELECTOR
Up to 256 channels can be selected via continuous rotation.

POWER ON/OFF, VOLUME UP/DOWN

AUDIO JACK
Supports different earpieces and remote speaker.

DISPLAY
Support displaying channel alias, caller ID and alias, zone number, battery indicator, high/low power, and signal intensity.

PUSH-TO-TALK BUTTON
Easy to find and touch.

PROGRAMMABLE BUTTON
It can be programmed for useful function you require.

BD502i

BD552i

PROFESSIONAL AND SIMPLE TO USE

A/D ANALOG & DIGITAL DUAL MODES
BD502i/BD552i can support both analog and digital modes on the same hardware. You can switch between two operation modes easily and it helps you to communicate with analog radios.

ANALOG & DIGITAL AUTO DETECT
BD502i/BD552i can detect the signal type when receiving a call, then automatically switches between analog mode and digital mode. During the call hang time, user can reply by using the push-to-talk. This is migration technology from analog to digital.

EXTENDED TALK RANGE
Based on Hytera innovative technology, your talk range is extended.

LONG WORKING TIME
Based on TDMA technology, BD5i series in digital mode can work upto 16 hours @ 1500mAh or 22 hours @ 2000mAh in 5-5-90 mode.

CLEAR VOICE
Excellent audio quality comes from the DMR digital technology, which makes communication more reliable.

RELIABLE AND DURABLE
BD502i/BD552i is compliant with MIL-STD-810 G and IP54.

ANTI-INTERFERENCE
Adopted digital encoding and error correcting module, BD5i series has the ability to avoid signal interference on the same frequency.

DMR DMR SIGNALING
With DMR signaling, transmitting group call, private call and all call with PTT ID becomes quite easy.

REPEATER MODE OPERATION
Utilize a DMR Tier II repeater to extend your communication range.

VOICE ANNOUNCEMENT (only for BD502i)
Channel number announcement helps you to switch channels quickly and correctly, even in operations with low visibility.

VOX
This feature allows you to activate the radio microphone via your voices volume, and frees your hand from PTT.

SCANNING
Allow BD5i series listening to communication activities on other channels.

ACCESSORIES

STANDARD ACCESSORIES

 <p>AN0435W09 Whip Antenna, 400-470MHz,^① 16cm</p>	 <p>BL1506 1500mAh Li-ion battery</p>	 <p>CH10L23 BD5i standard drop- in single unit charger</p>	 <p>BC08 Belt clip</p>	 <p>RO03 Nylon hand strap</p>	 <p>Power Adapter input: 100-240VAC, output: 12VDC/1A <i>US/UK/AU/EU/CHINA/JAPAN /KOREA</i></p>
--	---	--	--	---	---

OPTIONAL ACCESSORIES

 <p>EHM15 D-style earpiece with in-line PTT & MIC <i>VOXswitch</i></p>	 <p>EHM18 C-style earpiece with in-line PTT & MIC <i>VOXswitch</i></p>	 <p>ESM12 Ear-bud with PTT on MIC <i>VOXswitch</i></p>	 <p>EAM12 Ear-bud with PTT on MIC <i>VOXswitch</i></p>	 <p>EAM13 2-wire surveillance earpiece <i>VOXswitch</i></p>
 <p>ACM-01 PTT&MIC-only with 3.5mm jack <i>Ip54</i></p>	 <p>ES-01 Receive-only ear-bud</p>	 <p>ES-02 Receive-only surveillance earpiece</p>	 <p>EH-01 Receive-only C style earpiece</p>	 <p>EH-02 Receive-only earhook speaker</p>
 <p>PC76 Data programming cable</p>	 <p>SM08M3 Remote speaker microphone <i>with 3.5mm audio jack</i></p>	 <p>SM26M1^① Remote speaker microphone <i>Ip54 with 2.5mm audio jack</i></p>	 <p>LCBN13 Universal nylon chest Pack</p>	 <p>NCN011 Nylon carrying jacket</p>
 <p>BL2018 2000mAh Li-ion battery</p>	 <p>MCL19 BD5i multi-unit charger</p>	 <p>AN0435H13 Stubby antenna,400-470MHz,^② 9cm</p>	 <p>CHV09 Vehicle adapter (Input: 11-25V DC, Output: 12V DC & 1A)</p>	

① SM26M1 can be used with earpieces EA503,EHS17/18,ESS10.

② AN0435H13: 400-470MHz, 9cm AN0141H06: 136-147MHz, 17cm AN0167H06: 160-174MHz, 17cm AN0153H08: 147-160MHz/1575MHz, 12cm
AN0435W09: 400-470MHz, 16cm AN0153H07: 147-160MHz, 17cm AN0160H13: 146-174MHz, 15cm AN0167H07: 160-174MHz/1575MHz, 12cm

SPECIFICATION

General		
Frequency Range	UHF:400-470 MHz VHF:136-174 MHz	
Channel Capacity	BD502i: 48, BD552i: 256	
Zone Capacity	BD502i: 3, BD552i: 16	
Channel Spacing	25/12.5KHz	
Operating Voltage	7.2V	
Display	BD502i without display BD552i with display (0.91")	
Battery	1500mAh (Li-Ion) 2000mAh (Li-Ion)	
Battery Life (5/5/90)	Analog/Digital: 12/16 hours (1500mAh) 16/22 hours (2000mAh)	
Weight	BD502i: 240g, BD552i: 250g (With AN0435W09 and BL1506)	
Dimensions	BD502i: 108×54×28mm BD552i: 110×59×30mm	
Frequency Stability	±0.5ppm	
Antenna Impedance	50Ω	
Receiver		
Sensitivity (Digital)	0.22μV / BER 5%	
Sensitivity (Analog)	0.22μV (Typical) (12dB SIN AD) 0.4μV (20dB SIN AD)	
Adjacent Selectivity	TIA-603	60dB @ 12.5KHz/70dB @ 25KHz
Spurious Response Rejection	TIA-603	70dB @ 12.5/25KHz
Inter-modulation	TIA-603	65dB @ 12.5/25KHz
Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz	
Rated Audio Power Output	0.5W	
Rated Audio Distortion	≤3%	
Audio Response	+1 ~ -3dB	
Conducted Spurious Emission	<-57dBm	

Transmitter	
RF Power Output	VHF High power: 5W VHF Low power: 1W UHF High power: 4W UHF Low power: 1W
FM Modulation	11K0F3E @ 12.5KHz 16K0F3E @ 25KHz
4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz, -30dBm >1GHz
Modulation Limiting	±2.5KHz @ 12.5KHz ±5.0KHz @ 25KHz
FM Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Adjacent Channel Power	60dB @ 12.5KHz, 70dB @25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE+2™
Digital Protocol	ETSI-TS102 361-1,-2,-3

Environmental	
Operating Temperature	-30°C~ +60°C
Storage Temperature	-40°C~ +85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (Contact) ±15kV (Air)
Dustproof & Waterproof	IP54 Standard
Humidity	Per MIL-STD-810 G Standard
Shock & Vibration	Per MIL-STD-810 G Standard

All specifications are subject to change without notice due to continuous development.



Hytera America

3315 Commerce Parkway, Miramar, FL 33025, United States
Telephone: +1(954)846-1011

8 Whatney, Suite 200, Irvine, CA 92618, United States
Telephone: +1(949)326-5740

1916 Wright Boulevard, Schaumburg, IL 60193, United States
Telephone: +1 (213) 262-3578



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, **Hytera** are registered trademarks of Hytera Communications Co.,Ltd.
© 2018 Hytera Communications Co.,Ltd. All Rights Reserved.